

CHEM-7

the next-generation clinical chemistry analyzer



56 Direct Access Keys

Monitoring of Q.C.

Unique Triple Cuvette System

Low Reagent Consumption

Compact Design

Battery Backup Unit

Direct Printer / Keyboard Connectivity

Technical Specifications

Optical Module

- ~ Static photometer
- ~ 8 interference filters 340,405, 450, 505, 546, 578, 600 and 670 nm
- ~ Silicon photodiode detectors
- ~ Photometric Range from 0 to 2.5 OD
- Bandwidth + 8nm
- ~ Quartz Halogen Lamp of 12V, 20W

Measuring Module

- Unique Triple Cuvette System
 - •18 µl Flow cell
 - •10 mm Square Cuvette
 - 6 mm Round Glass Tube with Adaptor
- ~ Peltier Temperature Control: 25°C, 30°C, 37°C and Off
- ~ Peristaltic Pump
- \sim Minimum Aspiration Volume 200 μl

Analysis Modes (Endpoint, kinetic, fixedtime etc.

- ~ 1-point linear
- ~ Rate A non-linear
- ~ 2-point linear
- ~ 1-point sample blank linear
- ~ 1-point non-linear
- ~ 1-point sample blank non-linear
- ~ 2-point non-linear
- ~ Absorbance
- ~ Rate A linear
- ~ Coagulation

Memory

- ~ 200 User Defined Test Programs
- ~ 1000 Test Result
- ~ Reagent Blank
- ~ 2 Level QC

Result Recall

~ Collated Reports by date, ID or both

Built-in QC

- Daily and Monthly monitoring for 2 level Levy-Jenning QC Graphs

Display

- ~ High Resolution Graphics LCD with backlight.
- ~ View Area: 120 x 92 mm

Keyboard

- 41 Multifunction Keys and 6 dynamic keys

Printer

- In Built High Resolution Graphic Thermal Printer, kinetic graphs can be printed.

Interface

- ~ RS-232C Serial Port
- ~ Parallel Port
- ~ Port for External Keyboard

Power

- External Universal SMPS adapter
- ~ 18V DC, 100W, 90-264 V, 50/60 Hz.

Size(mm) and Weight

~ 205 (H) x 450 (W) x 300(D), Approx. 7 Kgs.


Optional Accessories

- External 16 Position Dry Block Incubator
- ~ External Battery Back-up

ERBA diagnostics Mannheim GmbH

Mallaustrasse 69-73, 68219 Mannheim / Germany Tel.: (+49) 0621 8799770

Fax: (+49) 0621 8799688 Email: sales@erbamannheim.com Website: www.erbamannheim.com



Multiple Calibration Modes



16 Position Dry Block Incubator



Battery Backup Unit



PC Keyboard Interface



Direct Patient Result Reporting



¹ Specifications are subject to change without prior notification. Accessories shown are not part of the standard accessories